

Pneumatic Yarn Cutting Head

Pneumatic yarn cutting head for cutting yarn made of various fibre materials. The cutting heads are used for cutting fiber strands, yarn and cables. They are primarily used for the automation of production and assembly processes.

CC32R/L

AIR INLET CONNECTION - 6mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D32X195L
CUTTING CAPACITY - 35000 dtex
WEIGHT - 0.97 kg

CF32R/L

AIR INLET CONNECTION - 6mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D32X182L
CUTTING CAPACITY - 10000 dtex
WEIGHT - 1.0 kg

7625R

FOR CF 32 CUTTER

7625L

CE41

AIR INLET CONNECTION - 6mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D41X203L
CUTTING CAPACITY - 35000 dtex
WEIGHT - 1.265 kg

CB29

AIR INLET CONNECTION - 4mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D29X118L
CUTTING CAPACITY - 15000 dtex
WEIGHT - 0.45 kg

CA29

AIR INLET CONNECTION - 4mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D29X142L
CUTTING CAPACITY - 15000 dtex
WEIGHT - 0.45 kg

CD29

AIR INLET CONNECTION - 6mm OD PIPE
OPERATING PRESSURE - 4-6 BAR
OVERALL DIMENSION - D40X135L
CUTTING CAPACITY - 15000 dtex
WEIGHT - 0.60 kg